









Technomed understands the importance of a crystal clear signal, ease of use and electrode durability.

Technomed's Reusable EEG Cup & Earclip Electrodes are designed to provide reliable signals and longtime ease of use.

The electrodes are designed for easy adjustment to the patient's contours to avoid electrode lift.

The electrode is designed with flexible wires and optimized connector for easy headbox insertion and extraction.

User Benefits

- Extra small reusable cup & earclip electrodes.
- Clear and reliable signal.
- Short cup-to-cable connection to reduce lift risk.
- Low profile disk with soft and flexible anti-tangle lead wires for high patient comfort.
- Optimized connector design for easy headbox insertion and extraction.
- Long electrode life with watertight design and Kevlar reinforced wires.

Reusable Cup Electrodes

Materials	Cup Size	Cup Height	Wire Length	Part Number
Silver Plated (Ag)	6 mm	1.7 mm	1.0 m	TE/C14-434
Silver Plated (Ag)	6 mm	1.7 mm	1.5 m	TE/C14-634
Silver Plated (Ag)	6 mm	1.7 mm	2.0 m	TE/C14-834
Gold Plated (Au)	6 mm	1.7 mm	1.0 m	TE/C34-434
Gold Plated (Au)	6 mm	1.7 mm	1.5 m	TE/C34-634
Gold Plated (Au)	6 mm	1.7 mm	2.0 m	TE/C34-834
Silver/Silver Chloride (Ag/AgCl)	6 mm	1.7 mm	1.5 m	TE/C24-634/99

Packing: sets of 12, 2 x 6 colors (red, green, white, yellow, blue, brown)





Specifications

Not made with natural rubber lat	ex √
REACH & RoHS (EU) compliant	$\sqrt{}$
Lead wire design	Tinsel wire
Lead wire core	Kevlar and Silver Plated Copper
Lead wire insulation	TPU
Spring loaded connector	Gold Plated Brass / PVC
Connector	DIN 42802-1

Cleaning and disinfection: see IFU for details



Reusable Ear Clip Electrodes

This product consists of two 6 mm or 10 mm diameter EEG cups mounted as an ear clip. Available in three different surface options: Silver-plated, Silver-Chloride or Gold-plated. The leadwires connect with a safety DIN 42 802-1 connector.


Cup Size	Cup Height	Wire Length	Part Number
6 mm	1.7 mm	1.0 m	TE/E14-439
6 mm	1.7 mm	1.5 m	TE/E14-639
6 mm	1.7 mm	1.0 m	TE/E34-439
6 mm	1.7 mm	1.5 m	TE/E34-639
6 mm	1.7 mm	1.0 m	TE/E24-439
6 mm	1.7 mm	1.5 m	TE/E24-639
10 mm	1.7 mm	1.0 m	TE/E12-439
10 mm	1.7 mm	1.5 m	TE/E12-639
10 mm	1.7 mm	1.0 m	TE/E32-439
10 mm	1.7 mm	1.5 m	TE/E32-639
10 mm	1.7 mm	1.0 m	TE/E22-439
10 mm	1.7 mm	1.5 m	TE/E22-639
	6 mm 6 mm 6 mm 6 mm 6 mm 6 mm 10 mm 10 mm 10 mm 10 mm	6 mm 1.7 mm 10 mm 1.7 mm	6 mm 1.7 mm 1.0 m 6 mm 1.7 mm 1.5 m 6 mm 1.7 mm 1.0 m 6 mm 1.7 mm 1.0 m 6 mm 1.7 mm 1.5 m 6 mm 1.7 mm 1.5 m 10 mm 1.7 mm 1.5 m 10 mm 1.7 mm 1.0 m 10 mm 1.7 mm 1.5 m

Packing: 1 pair

Specifications

DEHP < 0.1% by weight	
REACH & RoHS (EU) compliant	\checkmark
Lead wire design	Tinsel wire
Lead wire core	Kevlar and Silver Plated Copper
Lead wire insulation	TPU
Spring loaded connector	Gold Plated Brass / PVC
Connector	DIN 42802-1

Cleaning and disinfection: see IFU for details





Your Technomed Business Partner:
USA RX ONLY





Legal manufacturer: Technomed Europe

Amerikalaan 71 6199 AE | Maastricht-Airport | The Netherlands T +31 43 408 68 68 | info@technomed.nl

Technomed USA

7200 Medina Road, Suite 800 Plymouth | MN 55447 | United States - +1 651 288 0890 | info@technomed-usa.com